

packart.dev · Dieline catalogue

Bottle label 100 ml

PA-LB-005 · Label
Die extent: 120 × 50 mm (TrimBox)
Market: EU

Separations: Dieline (cut solid, crease 3/1.5 mm, perf 0.8/0.8 mm), Kiss cut, Technical, TP … — all non-printing, overprint.

Technical profile: Reel label · thermal transfer

Reel-fed labeller, TTO coding

1 LOT / EXP [Variable data / coding]
30 × 10 mm at 88 / 38 · Content: LOT, EXP · Method: Thermal transfer
Printed on the labeller after application check.

2 Thermal-transfer receptive area [Varnish-free area]
32 × 12 mm at 87 / 37

3 Unwind direction [Reading direction]
6 × 10 mm at 2 / 20 · Direction: right · Content: Unwind 4 (right edge leading)
Label leaves the reel with the right edge first.

4 GS1 DataMatrix [Serialisation (2D + HRI)]
14 × 14 mm at 103 / 3 · Content: GTIN (01) · SN (21) · LOT (10) · EXP (17) · Method: Thermal transfer
For labels that are the outer packaging.

Sample: parametric reconstruction of a standard style. Not a supplier die — not for production.
Generated 2026-11-08 20:43 UTC